ASTi Telestra & Voisus Matrix



T4H- XXXXXXX -XX

Processor

- 0: Dual Core
- 1: Quad Core
- 2: Multi Core (1st gen.)
- 3: Defined Performance
- 4: Defined Performance 2
- 5: Multi-core (2nd gen.)
- 6: Multi-core (3rd gen.)

Hard Drive

- 0: Removable hard drive (80GB min.)
- 1: No hard drive
- 2: Fixed hard drive
- 3: Fixed solid-state drive (SSD)
- 4: Upgraded hard drive
- 5: Removable SSD
- 6: Two removable SSDs
- 7: Two removable SSDs + one fixed SSD
- 8: Increased storage

Memory

- 0: 1GB RAM
- 1: 2GB RAM
- 2: 4GB RAM
- 3: 8GB RAM
- 4: 16GB RAM
- 5: 32GB RAM

Network Adapter

- 0: 2-port NIC (1st gen.)
- 1: No NIC installed (onboard only)
- 2: 4-port NIC (1st gen.)
- 3: 2-port NIC (2nd gen.)
- 4: 4-port NIC (2nd gen.)
- 5: 2-port NIC (3rd gen.)
- 6: 4-port NIC (3rd gen.)
- 7: n/a
- 8: 2-port NIC (4th gen.)
- 9: Dual 2-port NIC (4th gen.)
- A: 2-port NIC (3rd gen.) Flashed for iSCSI
- B: 4-port NIC (3rd gen.) Flashed for iSCSI

BIOS

- 0: Standard, dual-core
- 1: MBV
- 2: n/a
- 3: Standard, quad-core
- 4: Standard, multi-core
- 5: MicroServer
- 6: Multi-core with solid state
- 7: Unified Comms
- 8: MicroServer
- 9: Multi-core with solid state

Chassis

- 0: Non-standard 2U
- 1: Ruggedized
- 2: 1U chassis
- 3: Small form factor
- 4: Tower
- 5: MicroServer
- 6: Standard 2U
- 7: Standard 1U
- 8: Standard 4U
- 9: MicroServer

ASTi use only

Optical Drive

- 0: DVD-ROM drive
- 1: No DVD
- 2: DVD±RW drive

Telestra current production standard: T4H-55352-69 Voisus current production standard: VSH-55312-69

Not all T4H/VSH numbers are offered as customer-defined configurations.